

MB 002E

Belden's HD Designed Video Coaxial Cables Deliver:

- High Quality
- High Spec Technology
- High Performance
- Competitive Prices



Superior in Performance, Competitive in Price

Belden® broadcast cables have established a strong reputation for quality and reliability. In fact, they are setting the standard in HD applications around the world, ranging from major sporting events to daily news broadcasts. They are physically robust and require simple connectivity. With guaranteed Return Loss performance, these cables offer excellent picture quality and extended transmission distances. Sounds expensive? You may be surprised to learn that Belden broadcast cables can be superior in performance, yet competitive in price. Here we highlight the best of Belden broadcast cables, the first choice of broadcast professionals. See for yourself how Belden Broadcast cables set the standard.

10 Reasons to Choose Belden












- Belden's HD coaxes deliver 3G and exceed the standards. See the chart below for the maximum transmission distances
- Belden guarantees return loss (-23 dB from 5 MHz to 1.6 GHz and -21 dB from 1.6 GHz to 4.5 GHz)
- High-density nitrogen gas-injected foam dielectric used in the center core enable Installable Performance™
- High-density nitrogen-gas-injected foam resists deformation when bent or crushed delivering stable impedance and low return loss
- High quality and maximum consistency without connector issues and re-pulling of cable
- Very low attenuation
- All cables are available in halogen-free (direct burial, UV-resistant)
- Belden measure 75 ohms to 4.5 GHz to give the user real data for 1080p/50 applications
- Bundled versions (VideoFlex Et BananaPeel®) are available
- Belden HD coaxial cables deliver excellent picture quality and are deployed at major international sporting events because of our state-of-the-art technology

Transmission Distance

| Data Rate: | SD | | HD | | | | 3G | | |
|--------------|---------------|-----|--------------------------------|-----|------------------|--------|------------|-----|-----------|
| | 270 Mb/s | | 1.5 Gb/s | | | | 3.0 Gb/s | | |
| Spec: | SMPTE 292M | | SMPTE 259M (SMPTE 372M) | | | | SMPTE 424M | | |
| Application: | Component SDI | | 720p - 1080i (Dual Link 1080p) | | | | 1080p | | |
| Part No. | FT.* | M* | FT.* | M* | Independent Test | Genium | FT.* | M* | ThomsonGI |
| 179DT | 380 | 116 | 110 | 34 | 40 | | 80 | 24 | |
| 1855A | 790 | 241 | 260 | 79 | 80 | | 150 | 46 | 78 |
| 1855ENH | 856 | 261 | 284 | 87 | 100 | | 170 | 52 | |
| 1505F | 830 | 253 | 215 | 66 | 90 | | 145 | 44 | |
| 1505A | 1110 | 338 | 310 | 94 | 120 | | 220 | 67 | |
| 1694F | 1070 | 326 | 285 | 87 | 110 | | 190 | 58 | |
| 1694A | 1430 | 436 | 400 | 122 | 140 | 230 | 270 | 82 | 140 |
| 7855A | 1667 | 508 | 465 | 142 | | | 328 | 100 | |
| 7731A | 2040 | 622 | 550 | 168 | 230 | | 360 | 110 | 188 |

* calculated

Belden's HD Designed Coaxial Cable Portfolio Includes:

| | | |
|--|----------------|---|
|  | 179DT | DigiTruck, Low loss HDTV/SDI Digital video RG179 Coax, Duobond foil and 95% tinned copper braid, extremely small, lightweight and saves space |
|  | 1855A | Low loss HDTV/SDI Digital Video RG59/U Coax, 23 AWG Duofoil® and 95% tinned copper braid, recommended HD Distance: 80 m |
|  | 1855ENH | Loss HDTV/SDI Digital Video RG59/U Coax, 22 AWG Duofoil® and 90% tinned copper braid LSNH jacket, recommended HD Distance: 100 m |
|  | 1505A | Low loss HDTV/SDI Digital Video RG59/U Coax, 20 AWG Duofoil® and 95% tinned copper braid, recommended HD Distance: 120 m |
|  | 1505ANH | Low loss HDTV/SDI Digital Video RG59/U Coax, with LSNH jacket, recommended HD Distance: 120 m |
|  | 1505F | Low loss HDTV/SDI Digital Video RG59/U Coax, extremely flexible with double 98% braided, recommended HD Distance: 100 m |
|  | 1694A | Low loss HDTV/SDI Digital Video RG6/U Coax, 18 AWG Duofoil® and 95% tinned copper braid, recommended HD Distance: 140 m |
|  | 1694ANH | Low loss HDTV/SDI Digital Video RG6/U Coax, with LSNH Jacket, recommended HD Distance: 140 m |
|  | 1694F | Low loss HDTV/SDI Digital Video RG6/U Coax, extremely flexible with double 98% braided, recommended HD Distance: 120 m |
|  | 7731A | Low loss HDTV/SDI Digital video RG11/U, 14 AWG Duofoil® and 95% tinned copper braid, recommended HD Distance: 230 m |
|  | 7731ANH | Low loss HDTV/SDI Digital video RG11/U, 14AWG Duofoil® and 95% tinned copper braid, with LSNH jacket, recommended HD Distance: 230 m |

For more information on these products please go to
<http://www.beldenemea.com/entertainment>

We appreciate that in most cases one size does not fit all and that you may have some specific requirements. As the world's leading supplier of high quality broadcast cables, Belden® has a wide choice of products and superior technical support to ensure that you get exactly what you need. For more information, please contact: